



What Are The Options?

Omni-Plant™ 270°

- 12/24 volt system
- Three analogue HD cameras
- A range of monitors
- 50/50 splitscreen



Omni-Plant™ 360°

- 12/24 volt system
- Four analogue HD cameras
- A range of monitors
- 50/50 splitscreen



Omni-Plant™ 270° Digital HD

- 12/24 volt system
- Three cameras with crisp 720p visuals
- 7"/10" digital monitor
- 50/50 splitscreen



Omni-Plant™ 360° Digital HD

- 12/24 volt system
- Four cameras with crisp 720p visuals
- 7"/10" digital monitor
- 50/50 splitscreen



Our Service

- National installation
- Bespoke calibration
- UK-based support

Surround-View (SV) systems provide the driver with a complete 360° view around the vehicle.

The 'split screen' monitor displays:

- A permanent 'look down' view from above, showing the vehicle and its surroundings
- Automatically triggered individual camera views (left camera when indicating left; right camera when indicating right; rear camera when reversing)

Four (or three) ultra-wide angle cameras (front, left, right and rear) are connected to an Electronic Control Unit (ECU), which 'stitches' the images together to form a seamless 'look down' view.

The benefits of Surround-View include:

- Elimination of all blind spots
- Clear visibility of site workers and hazards
- Reduced likelihood of accidents and incidents
- Evidence recording (when specified with an optional DVR - see overleaf for details)



Omni-Plant™ 270°/360°

Suitable for machines/plant of all sizes.

- 12/24 Volt
- Keybox included as standard (enables manual camera selection - does not need to be utilised)
- Utilises four (or three) 1.3MP/WDR cameras
- 184° ultra-wide angle
- IP69K
- Views are tailored to meet user requirements and/or compliance standards
- Choose from a range of plastic and metal/waterproof monitors
- Compatible with four-channel and two-channel DVRs
- 30 frames-per second



Omni-Plant™ 270°/360° Digital HD

Suitable for machines/plant of all sizes, utilising the latest **digital HD** technology for superior resolution

- 12/24 Volt
- Keybox included as standard (enables manual camera selection - does not need to be utilised)
- Utilises four (or three) **digital HD** 720p/WDR cameras
- 190° viewing angle
- IP69K
- Views are tailored to meet user requirements and/or compliance standards
- 7" or 10" **Digital HD** monitor
- Compatible with four-channel and two-channel **Digital HD** DVRs
- 30 frames-per second (720p)



Monitor Options

Omni-Plant™ 360° System Monitor Options

- GP 7"
- 'Standard' 7" with 'touch buttons'
- GP 7" waterproof monitor
- "Superior' 7" waterproof monitor


Omni-Plant™ 360° Digital HD System Monitor Options

- 7" Digital HD Dash Mounted
- 10" Digital HD Dash Mounted

Recording

DR-400N (128GB SSD)

- Four recording channels
- Up to 1TB storage capacity
- Records at 30fps
- Secured hard drive tray
- GPS and 3-axis g-sensor



DR-120 (16GB SD)

- Two recording channels
- Up to 128GB storage capacity
- Records at 30fps
- AV-out connection



1GB provides approximately 1 hour of high-resolution video storage

01733 246473/sales@trailervision.co.uk/www.trailervision.co.uk